

CONCRETE STAINS FOR EVERY APPLICATION!

CoolStain^{PRO}



The ORIGINAL
Solid Color Stain



SMARTCOLOR



Designer Series
Enhancer



The Translucent
Color Enhancer



Description	Patent-pending, infrared reflective stain reduces the surface temperature of treated concrete by up to 50° F! Restores the beauty of concrete by covering blotchy marks, discolorations, failed acid stain or faded integral color.	The original solid stain used to restore ugly concrete to make it look brand new again! Completely covers existing stains, discolorations, blotchy concrete, failed acid stain or faded integral color and leaves a natural-looking finish, too!	Patent-pending, concrete stain decorates and revitalizes concrete surfaces with strong hiding capacity and a natural look; user-friendly and safe alternative to unreliable and hazardous solvent or acid-based stains.	Semi-transparent stain used to faux finish over the ORIGINAL Solid Color Stain or existing concrete finishes. Can be used to match the mottled, variegated finish of reactive stains.	Translucent stain designed to be used over the ORIGINAL Solid Color Stain in a contrasting color to create a two-toned, antiqued finish for stamped / textured concrete surfaces.
Cost PSF	41¢ at suggested contractor price	34¢ at suggested contractor price	14¢ at suggested contractor price	12¢ at suggested contractor price	9¢ at suggested contractor price
Avg. Opacity %	100% (completely opaque)	100% (opaque)	75% (semi-opaque)	75% (semi-transparent)	50% (translucent)
Formula Base	Polymer-modified	Polymer-modified	Nano-acrylic	Polymer-modified	Polymer-modified
Colors	20 standard colors	80 standard colors	26 standard colors	80 standard colors	80 standard colors
Installed with:	NewLook Applicator Brush	NewLook Applicator Brush	Airless or HVLP sprayer	HVLP sprayer	Garden pump sprayer or brush
Components	3 components	4 components	1 component	3 components	3 components
Shelf Life	2 years	2 years	4 years	2 years	2 years
Pot Life	3 to 5 hours	3 to 5 hours	3 months	3 to 5 hours	3 to 5 hours
Sealer Req'd?	No (see tech data)	No (see tech data)	Yes (e.g. SmartSeal™)	Yes	Yes
Application	Exterior only	Interior & exterior	Interior & exterior	Mostly interior	Mostly exterior
New Concrete	Wait 28 days	Wait 28 days	Wait 7 days	Wait 28 days	Wait 28 days
CSP* Req'd.	2 (See www.ICRI.org)	2	1	2	2